



MODEL: **A3000MN - METRO 2**

THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity
-20°C*

Cubic Capacity
9.84m³

BODY DIMENSION

External length	3000mm
External width	2100mm
External height	1950mm
Internal length	2840mm
Internal width	1980mm
Internal height	1750mm
Pallet loading	2 Pallet capacity

Fitted body weight *840kg

PANELS THICKNESS

Roof/floor	100mm
Front wall/rear doors	80mm
Side walls	60mm

Side door	Passenger side pallet door 1750 x 1400mm
Rear door	Double - (left opens first)
Front wall frame	Universal to suit off engine drive units
Side step	Fixed rung step
Rear step	Fixed plank step
Cargo track	1 recessed row @ 750mm 1 shoring bar
Floor	One piece aluminium ricegrain
Internal light	1 LED sensor light
Refrigeration	*Thermo King SV-400



Thermal efficiency 'K' VALUE .47 W/m²K tested to Australian Standard AS4982

Standard Inclusions

Model No: A3000MN - BDEHI - METRO 2

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor light
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint with bar supplied
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements

