

THERMAXX ADVANTAGE THE ADVANTAGE IS TO YOUR BOTTOM LINE		
BODY DIMENSION External length	3000mm	Side door
External width External height	2100mm 2000mm	Rear door
Internal length	2860mm	Front wall f
Internal width Internal height	1980mm 1800mm	Side step
Pallet loading	2 Pallet capacity	Rear step
Fitted body weight	*840kg	Cargo tracl
PANELS THICKNESS	100mm 80mm 60mm	Floor
Roof/floor Front wall		Internal ligh
Side walls/rear/side doors		Refrigeration

Side door	Passenger side single door 1800 × 800mm
Rear door	Triple - (centre opens first)
Front wall frame	Universal to suit off engine drive units
Side step	Fixed rung step
Rear step	Fixed plank step
Cargo track	I recessed row @ 750mm I shoring bar
Floor	One piece aluminium ricegrain
Internal light	I LED sensor light
Refrigeration	*Thermo King SV-400

-20°C\*

10.19m<sup>3</sup>



## Thermal efficiency 'K' VALUE .47 W/m<sup>2</sup>K tested to Australian Standard AS4982

## **Standard Inclusions**

## **Model No: A3000N - ACEHI - CITY BOXX**

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame

- Recessed stainless door hardwar
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor light
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint with bar supplied
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements



