



MODEL: **A4060N**

THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity
-20°C*

Cubic Capacity
14.18m³

BODY DIMENSION

External length	4060mm
External width	2180mm
External height	2000mm
Internal length	3900mm
Internal width	2020mm
Internal height	1800mm
Pallet loading	3 Pallet capacity

Fitted body weight *1177kg

PANELS THICKNESS

Roof/floor	100mm
Front/side wall	80mm
Rear/side doors	80mm

Side door	Passenger side single door 1450 x 650mm
Rear door	Double - (left opens first)
Front wall frame	Universal to suit off engine
Dividing wall	Option
Rear step	Fixed plank step
Side step (option)	Fixed rung or fold down step
Cargo track	1 recessed row @ 800mm 1 shoring bar
Floor	Fibreglass non-slip
Internal light	2 LED sensor lights
Refrigeration	*Thermo King SV-400
Option	*V-500 for 2 zone fridge



Thermal efficiency 'K' VALUE .34 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights

Model No: A4060N - BCFHI

- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Options available to suit customer requirements

