



**THERMAXX** ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity  
-20°C\*

Cubic Capacity  
19.38m<sup>3</sup>

#### BODY DIMENSION

External length	4200mm
External width	2490mm
External height	2200mm
Internal length	4020mm
Internal width	2410mm
Internal height	2000mm
Pallet loading	6 Pallet capacity

**Fitted body weight** \*1428kg

#### PANELS THICKNESS

Roof/floor	100mm
Front wall	100mm
Side walls/side doors	40mm
Rear doors	80mm

Side door	Passenger side pallet door 2000 x 1400mm
Rear door	Triple - (centre opens first)
Front wall frame	Universal to suit off engine or diesel drive units
Side step	Fixed rung step
Rear step	Fixed plank step
Cargo track	1 recessed row @ 800mm 1 shoring bar
Floor	One piece aluminium ricegrain
Internal light	2 LED sensor lights
Refrigeration Option	*Thermo King SV-400 *Thermo King SV-600



Thermal efficiency 'K' VALUE .59 W/m<sup>2</sup>K tested to Australian Standard AS4982

## Standard Inclusions

## Model No: A4200P - ADEHI PREMIUM

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements

