



THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

A7800P

Temperature Capacity
-20°C*

Cubic Capacity
44.99m³

BODY DIMENSION

External length	7800mm
External width	2490mm
External height	2650mm
Internal length	7620mm
Internal width	2410mm
Internal height	2450mm
Pallet loading	12 Pallet capacity

Fitted body weight *2964kg

PANELS THICKNESS

Roof/floor	100mm
Front wall	100mm
Side walls/side doors	40mm
Rear doors	80mm

Side door	Passenger side pallet door 2450 x 1400mm
Rear door	Double - (left opens first)
Front wall frame	Universal to suit diesel drive units
Side step	Fixed rung step
Rear step	Heavy duty crash bar
Cargo track	2 recessed rows @ 800-1400mm 2 shoring bars
Floor	One piece aluminium ricegrain
Internal light	3 LED sensor lights
Refrigeration	*Thermo King T-1000R



Thermal efficiency 'K' VALUE .57 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements

Model No: A7800-BDEHI

