



**THERMAXX** ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

MODEL: **A9000P JUMBO**

Temperature Capacity  
-20°C\*

Cubic Capacity  
57.39m<sup>3</sup>

#### BODY DIMENSION

External length	9000mm
External width	2490mm
External height	2900mm
Internal length	8820mm
Internal width	2410mm
Internal height	2700mm
Pallet loading	14 Pallet capacity

**Fitted body weight** \*3420kg

#### PANELS THICKNESS

Roof/floor	100mm
Front wall	100mm
Side walls/side doors	40mm
Rear doors	80mm

Rear door	Double (left opens first)
Front wall frame	Universal to suit diesel drive units
Side step	N/A
Rear step	Heavy duty crash bar
Cargo track	3 recessed rows @ 900-1500mm -1800mm 3 shoring bars
Floor	One piece aluminium ricegrain
Internal light	4 LED sensor lights
Refrigeration	*Thermo King T-1200R



Thermal efficiency 'K' VALUE .55 W/m<sup>2</sup>K tested to Australian Standard AS4982

### Standard Inclusions

### Model No: A9000P - BEHI JUMBO

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements
- 2 Lock rods per door

